









LB-282 Upright Binocular Fluorescent Microscope with Infinite Optical System, Plan Achromatic Objectives and B, G, UV and V Excitation Filters

Affordable price Advanced design Including four filters of UV, V, G and B



## LB-282 Upright Binocular Fluorescent Microscope with Infinite Optical System, Plan Achromatic Objectives and B, G, UV and V Excitation Filters

## Introduction

LABOMEDING

LB-282 Upright Binocular Fluorescent Microscope with Infinite Optical System, Plan Achromatic Objectives and B, G, UV and V Excitation Filters are a kind of cost effective advanced laboratory microscope which is designed for the area of medicine, clinical and biology research. It is equipped with infinity Plan Achromatic optical system, chromatic aberrations and curvation of field, that are both ideally corrected over the field of view.

## **Technical Specifications**

Optical system: Infinity optical system F=200

Viewing head: Seidentopf Binocular head, inclined 30 degree, 360 degree rotatable, diopter adjustment,

Interpupillary distance 52-75mm

Eyepiece: 10X/20mm, high eye-point up to 21mm

Focusing: Coaxial Coarse and fine focusing knob, height adjustable

Objectives: Plan achromatic objectives 4x,10x, 40x, 100x

Condenser: Abbe condenser NA 1.25 with Iris diaphragm, socket to accommodate PH-slide.

Condenser center adustable, Color-coded diaphragm scale markings coresponded with the

objectives of difficult power.

Stage: Double layer stage: 156x138mm platform, X/Y travel of 76x54mm by low positioned

X/Y coaxial control knob, scale mark and specimen-slide clip, enough space to hold

2 specimen slide.

Nosepiece: Quadruple

Koehler illumination: With field diaphragm

Filter: Blue

Filter holder: For more than one filter

Reflected Fluorescent

Attachment: DC Hg fluorescent lamp house 100W

Mercury lamp 100w

Filter Turret UV shield

DC Hg power source house 100W

Fuse 250V/5A phi 5x20

B Excitation filter G Excitation filter UV Excitation filter V Excitation filter

Illumination: 6V 20W Osram Halogen bulb

Immersion oil:8mlAllen Screw Driver:Phi 2mmPower line:1.8m

Package: Inner package: Foam, Plastic bag; out package; Carton

