

HUMAN Lab® WS series



WSB-08F

WSB-04F

### 1 Features

- This general lab. water still remove most dissolved solids and pyrogens from tap water or pretreated water.
- Water Still features a thermostat and a water level switch provides automatic operation.
- Protect from over-heating by cut-off when feed water interrupted.
- Easy to clean by removing the condenser from the body.
- The stainless steel double-walled chamber saves electricity.

### 2 Specifications

Model	WSB-04F	WSB-08F
Capacity	3.5 l / hour	7 l / hour
Cooling water	30 l / hour	60 l / hour
Heater	3 Kw	6 Kw
Material	Stainless steel Interior & Steel sheet Exterior	
Safety Device	Water level float switch, Over temp. thermostat Water supply cut-off valve	
Power source	220VAC, 50/60Hz	
Overall (WxDxH)	400 x 225 x 545mm	460 x 260 x 610 mm
Weight (Kg)	20	23

## Automatic Water Still

### 1 Features

- These water still produce pure and pyrogen-free distillates with fully automatic boiler.
- Automatic operation switches unit off when reservoir is full.
- Built-in stainless steel storage tank for distillation
- Sensing water level in boiling chamber to protect heater from over heating
- Check water level in reservoir to start / stop distillation automatically.
- East to use and maintenance free

### 2 Specifications

Model	WSA-04	WSA-08	WSA-12
Capacity	3.5 l / hr	7.0 l / hr	10 l / hr
Cooling water	30 l	60 l	90 l
Heater	3 Kw	6 Kw	9 Kw
Reservoir	11 liter	20 liter	25 liter
Power source	220VAC,50/60Hz,single phase		
Overall (WxDxH)	730x430x580mm		750x450x580
Weight (Kg)	28	35	42
Model	WSA-04-D	WSA-08-D	
Capacity	3.5 l / hour	7 l / hour	
Cooling water	45 l	90 l	
Heater	9 Kw	12 Kw	
Material	Stainless steel Interior & Steel sheet Exterior		
Reservoir	11 liter	20 liter	
Safety Device	Water level float switch, Over temp. thermostat Water supply cut-off valve		
Power source	220 VAC,50/60Hz,3 phase		
Overall (WxDxH)	730x700x570mm		
Weight (Kg)	58	60	



Single Water Still  
(WSA-04/08)



Double Water Still  
(WSA-04/08-D)